



Bobcat®

COMPACT TRACTORS

CT2035 / CT2040

Engine power (PTO)	35HP / 38HP (31HP / 32.1HP)
Lifting Capacity	740 kg.f
Transmission Type	HST



One Tough Animal.

CT2035 / CT2040 - SPECIFICATIONS

Engine	CT2035	CT2040
Fuel	Diesel	Diesel
Gross Horsepower	35.0 HP	38.0 HP
No. of Cylinders	3	3
Total Displacement	1826 cc	1826 cc
Fuel Tank Capacity	34.0 L	34.0 L

3-Point, PTO & Hydraulics

	CT2035	CT2040
PTO Horsepower (Average PTO Horsepower)	31.0 HP	32.1 HP
3-Point Hitch	Category 1	Category 1
Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System
Hydraulic Lift Capacity at 24 in. Beyond Lift Point	740 kg.f	740 kg.f
Rear PTO	540 rpm	540 rpm
Rear PTO System	Live	Live
Mid-PTO	Optional: 2000 rpm	Optional: 2000 rpm
Total Hydraulic Pump Capacity	44.4 L/min	44.4 L/min
Rear Hydraulics	Std (4)	Std (4)
Lower Links	Ball	Ball
Lifting Rod	Turn-buckle	Turn-buckle

Drive System

	CT2035	CT2040
Transmission	HST	HST
Speed Ranges	3 Range	3 Range
Brakes	Wet Disc Type	Wet Disc Type
Rear Differential Lock	Rear Standard	Rear Standard
Four-Wheel Drive	STD-Mechanical	STD-Mechanical

Travel Speeds (w/ Ind. Tires)

	CT2035	CT2040
Forward	0 - 23.9 km/h	0 - 23.9 km/h
Reverse	0 - 21.5 km/h	0 - 21.5 km/h

Dimensions

	CT2035	CT2040
Overall Length (w/ 3 pt.)	3070 mm	3070 mm
Overall Width (w/ industrial tires)	1595 mm	1595 mm
Overall Height (w/ ROPS)	2650 mm	2650 mm
Wheelbase	1670 mm	1670 mm
Ground Clearance	340 mm	340 mm
Weight	1240 kg	1240 kg

Steering

	CT2035	CT2040
Inside Turning Radius	2450 mm	2450 mm
Hydrostatic Power Steering	Standard	Standard

Safety Equipment

	CT2035	CT2040
Fold Down ROPS (roll-over protective structure)	Std	Std
Fully Retractable Seatbelt	Std	Std

Standard Features

	CT2035	CT2040
Suspension Seat	Glow Plug Engine Pre-heat	Glow Plug Engine Pre-heat
Adjustable Seat	Head Lights/Tail Lights	Head Lights/Tail Lights
Linked Pedal	Cruise Control	Cruise Control
Cup Holder	Horn/Hazard Flasher/Turn Signals	Horn/Hazard Flasher/Turn Signals

Option List

CT2035	CT2040
Rear Working Lights	Rear Weight
Front Weight	Clevis Type Drawbar
Sun Canopy	Tool Box Kit
MID PTO Kit	Rear View Mirror Kit
7 Pin Socket Kit	

Front-End Loader (4in1 bucket)


CT2035	CT2040
Max. Lift Height to Pivot Pin	2451 mm
Max. Lift Height under Level Bucket	2284 mm
Clearance with Bucket Dumped	1830 mm
Reach at Maximum Lift Height	556 mm
Maximum Dump Angle	54°
Reach with Bucket on Ground	1600 mm
Maximum Rollback Angle	41°
Digging Depth	111 mm
Lift Capacity at Pivot Pin (max. height)	654 kg
Rollback Force at 500 mm (at Ground level)	954 kg
Weight (with Bucket)	490 kg
Bucket Capacity (Heaped Capacity)	0.19 m ³
Bucket Widths	1524 mm

Backhoe

CT2035	CT2040
Digging Depth (2' flat bottom)	2286 mm
Reach from Center Line of Swing Pivot	3099 mm
Loading Height (bucket at 60°)	1880 mm
Maximum Leveling Angle	8°
Swing Arc	180°
Transport Height (maximum)	2121 mm
Bucket Rotation	180°
Stabilizer Spread (down position)	1994 mm
Stabilizer Spread (up position)	1626 mm
Bucket Digging Force	1395 kgf
Operating Pressure	2466 psi (170 bar)
Shipping Weight (without bucket)	399 kg



Bobcat is a Doosan company.
Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.
©2020 Bobcat Company. All rights reserved.



Bobcat[®]

Doosan Bobcat Korea Co., Ltd.

www.bobcat.com